

CDZ3202HDS 2 MegaPixel HD-SDI

Infrared Speed Dome Camera

Features:

- 1/2.8" Exmor CMOS Sensor
- 20x optical zoom,12 digital zoom
- 2Mp HD SDI high resolution
- DNR(2D&3D)
- 150m IR range 8pcs OSRAM lens
- WDR
- IP66 rating
- Auto tracking and wiper



Specifications:

| | | |
|---------------|--------------------------|--|
| Camera | Image Sensor: | 1/2.8" Exmor CMOS (W20B Korea camera module) |
| | Effective Pixels: | 2.0M Pixels HD SDI video image |
| | Zoom: | Optical zoom:20X Digital zoom:32X |
| | Focal Length: | f=4.7-94.0mm |
| | Aperture Range: | F1.6-F3.5 |
| | Angle of View: | 55.4°-2.9°(Wide-Tele) |
| | Day& Night: | Auto/Day/Night/Ext |
| | Focus Mode: | Auto /Manual / One Push |
| | S/N Ratio: | >50dB |
| | BLC: | ON/OFF |
| | White Balance: | Auto / Manual /Indoor /Outdoor/One Push |
| | Shutter Time: | 1/1-1/60,000sec |
| | AGC: | Off/On(Max.42dB) |
| | Min.illumination: | Color:0.5lux B/W:0.1 lux Color DSS:0.002lux B/W DSS:0.001 lux |

| | | |
|-----------------------|---------------------------------------|---|
| | WDR: | Support |
| | Video Output: | HD: digital(LVDS) |
| IR Leds | IR Led: | 8 Germany OSRAM array IR leds |
| | IR Range: | 150m |
| | IR Action Mode: | Auto/Manual/Camera |
| | IR Led Power: | 30W |
| Pan & Tilt | Pan Range: | 360° endless |
| | Pan Speed: | Pan Manual Speed: 0.01°-360°/s, Pan Preset Speed: 360°/s |
| | Tilt Range: | -5°-90° (Auto Flip) |
| | Tilt Speed: | Tilt Manual Speed: 0.1°-120°/s, Tilt Preset Speed:120°/s |
| | Number of Preset: | 256 |
| | Patrol: | 8 patrols, up to 32 presets per patrol |
| | Auto Scan: | 8 scans with settable left and right boundaries |
| | Pattern: | 4 patterns, up to 500 instructions per pattern |
| | Protocols | Auto Compatible PELCO_P, PELCO_D |
| General | OSD Menu: | Graphical menu |
| | VAL: | Support |
| | Auto Tracking: | Support (Optional) |
| | Quickly Installation: | Support |
| | Wiper: | Standard Configuration(Optional) |
| | Power Box: | Optional |
| | Power Supply : | DC12V+-10% |
| | Power Consumption: | 45W |
| | Working Temperature /Humidity: | -35°C-+55°C 90% or less(No Condensing) |
| | Protection Level: | IP66 standard (outdoor dome),Level 2 lightning protection, 3000V surge protection |
| | Mounting: | Various mounting modes option:wall-mount,pendant-mount |
| | Accessories: | Wall-mount bracket, Protective sling,Power adapter(DC12v) |

| | | |
|--|-------------------------|--|
| | Weight(approx.): | 5kg |
| | Accessories: | Wall-mount bracket, Protective sling, Power adapter(DC12v) |

Dimension:

